



TYPE 'A'
LOT CORNERS

TYPE 'B'
STREET MONUMENTS

TYPE 'C'
STREET MONUMENTS

NOTES:

1. LOT CORNERS SHALL BE MARKED WITH MONUMENT 'A'. STATE LAW REQUIRES ALL CORNERS TO BE TAGGED WITH SURVEYOR'S NUMBER.
2. STREET MONUMENTS FOR GOVERNMENT CORNERS AND SUBDIVISION BOUNDARY CORNERS SHALL BE 2" x 18" MINIMUM. OTHER STREET MONUMENTS FOR CENTERLINE, INTERSECTIONS, ETC....SHALL BE 3/4" x 18" MINIMUM.
3. TYPE 'C' STREET MONUMENTS SHALL BE USED TO LOCATE ALL ANGLE AND CURVE POINTS ON THE CENTERLINES OF ASPHALT CONCRETE SURFACED SUBDIVISION STREETS.
4. ADDITIONAL MONUMENTS MAY BE REQUIRED AT THE DISCRETION OF THE CITY ENGINEER.
5. CONCRETE SHALL BE CLASS 560-C-3250 W/4" SLUMP MAX. PER SECTION 201 OF STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (CURRENT EDITION).